

Material Data Sheet No. 001

The **ANACONDA Hose Clips** are ideal for connecting and fastening all types of hoses in a wide range of branches. A fundamental principle is the worm-type mounting of the screw in the middle of a clip that guarantees a strong connection and high joint tightness. Clip assembly and disassembly are very simple; a common screw or hexagon screwdriver may be used.

ANACONDA hose clip materials and ANACONDA Spring clamps W1, ANACONDA Mini Hose clamps:

W1 – The clip band and house are made of galvanized steel.
Screw – galvanized steel with blue chromate.

W2 – The clip band and house are made of stainless steel.
Screw – galvanized steel with blue chromate.

W4 – The whole clip – the band, house and screw – are made of stainless steel

W5 – The whole clip – the band, house and screw – are made of stainless steel with an increased salt water and acid resistance. Antimagnetic.

Information on the tightening torques of ANACONDA hose clips.

ANACONDA W1 Hose Clip

Range of Clamping in mm	Band Width	Recommended Tightening Torque	Destructive Tightening Torque
8-12	9 mm	2.5-3.0	4.5
10-16	9 mm	3.0-3.5	4.7
12 - 20	9 mm	3,0 - 3,5	4,9
16 - 25	9 mm	3,0 - 3,5	5,2
20 - 32	9 mm	3,0 - 3,5	5,5
25 - 40	9 mm	3,0 - 3,5	6,0
32 - 50	9 mm	3,0 - 3,5	6,0
40 - 60	9 mm	3,0 - 3,5	6,0
50 - 70	9 mm	3,0 - 3,5	6,0
60 - 80	9 mm	3,0 - 3,5	6,0
70 - 90	9 mm	3,0 - 3,5	6,0
80 - 100	9 mm	3,0 - 3,5	6,0
90 - 110	9 mm	3,0 - 3,5	6,0
100 – 120	9 mm	3,0 - 3,5	6,0
110 - 130	9 mm	3,0 - 3,5	6,0
120 - 140	9 mm	3,0 - 3,5	6,0
130 - 150	9 mm	3,0 - 3,5	6,0
140 - 160	9 mm	3,0 - 3,5	6,0

Larger ranges of clamping can only be made to order.